# XFE 15 150 18.0-EC

**Random orbital polishers remove material gently for reliable results. That makes them ideal for beginners.**




**Technical features**

- Electronic management system (EMS) protects the tool, extends its service life and increases efficiency
- Brushless motor with greater efficiency and a longer service life
- LED battery capacity capacity indicator
- Free-running drive for hologram-free finishing
- 15 mm polishing stroke for high efficiency
- Accelerator trigger switch for a slow and sensitive start
- Cushioned special hook and loop backing pad for polishing
- Very smooth running thanks to to balancing mass
- Flat gear head reduces the distance from the surface.
- Handle cover: ergonomically shaped with SoftGrip.
- Low heat generation on the surface makes it ideal for temperature-sensitive paints

**Cordless eccentric polisher for:**

- Vehicle cleaners
- Car repair shops
- Smart repairs
- Aviation
- Car dealers
- Maritime
- Acrylic glass industry




**Technical data**

| | |
|---|---|
| Max. polishing pad Ø | 160 mm |
| Max. backing pad Ø | 150 mm |
| Stroke | 15 mm |
| No-load speed | 2300-3800/min |
| Stroke rate at no-load | 4600-7600/min |
| Battery voltage | 18 V |
| Battery capacity | 2.5 / 5.0 Ah |
| Average battery runtime 2.5 Ah | up to 20 min |
| Average battery runtime 5.0 Ah | up to 45 min |
| Weight excluding battery | 2.1 kg |
| Weight with 5.0 Ah battery | 2.8 kg |

## XFE 15 150 18.0-EC C

**Supplied in a box**

**Standard equipment**

- Special hook and loop
  1 backing pad Ø 125 mm
  1 backing pad Ø 150 mm

Order No.

493864

## XFE 15 150 18.0-EC

**Standard equipment**

- 1 special hook and loop backing pad Ø 125 mm
- 1 special hook and loop backing pad Ø 150 mm
- 1 carrying case L-BOXX® 238
- 1 case insert



Order No.

459089

## XFE 15 150 18.0-EC/5.0 Set

**Standard equipment**

- 1 special hook and loop backing pad Ø 125 mm
- 1 special hook and loop backing pad Ø 150 mm
- 2 rechargeable batteries 5.0 Ah AP 18.0/5.0
- 1 charger CA 10.8/18.0
- 1 carrying case L-BOXX® 238
- 1 case insert



Order No.

418099

## XFE 15 150 18.0-EC/5.0 P-Set

**Standard equipment**

- Special hook and loop
  1 backing pad Ø 125 mm
  1 backing pad Ø 150 mm
- 1 polish P03/06-LDX 250 ml
- 1 sealant W02/04 250 ml
- 1 microfibre cloth MW-PC
- 1 polishing sponge PS-0 160
- 1 polishing sponge PS-R 160
- 2 rechargeable batteries 5.0 Ah AP 18.0/5.0
- 1 charger CA 10.8/18.0
- 1 carrying case L-BOXX® 238
- 1 case insert



Order No.

461237