www.flex-tools.com

this is proformance FLEX

ORE 3-150 18-EC

18 V cordless random orbit sander with speed control

Order no. 534185

GTIN 4030293280250



- Lightweight, compact one-handed random orbital sander, very ergonomic and low-vibration thanks to special balancing for fatigue-free and joint-friendly work
- Sanding speed suitable for the material thanks to electronic speed adjustment
- Electronics: Speed preselection with 4 settings
- Ergonomically designed, handy grip cover with soft grip insert ensures a secure grip and good guidance
- E-signal switch for simple, safe operation with quick-stop function prevents trailing of the backing pad
- Equipped with disc brake, as a result no unwanted sanding marks are produced on the workpiece and expensive corrective finishing is not required
- External dust extraction Ø 27 mm, antistatic suction hose SH 27x3,5m AS (445.045) can be connected
- Integrated dust extraction with dust filter bag
- Velcro backing pad with multi-hose system for optimum extraction, suited to all standard 150 diameter abrasives
- Brushless motor with greater efficiency and a longer service life
- Electronic management system (EMS) protects the machine, extends the service life, and increases efficiency
- LED battery capacity display
- FLEX battery system: suitable for FLEX 18,0 V/5,0/2,5 Ah battery packs. Delivery does not include battery and charger



Technical data

Battery voltage	18 V
Battery capacity	2.5 / 5.0 Ah
Backing pad diameter	150 mm
Stroke	3 mm
No-load speed	4000 - 10000 rpm
Orbit rate, no load	8000 - 20000 rpm
Diameter dust extraction connection	Ø 27
Dimensions WxLxH	220 x 150 x 135 mm
Weight without battery pack	1.23 kg
Sound pressure level	81 dB(A)
Vibration	3.92 m/s²

Standard equipment

1 Dust bag (534188)
1 Adapter, short (532094)
1 Adapter, long (532095)
1 Carrying case L-BOXX® (414093)
1 Case insert (536119)