Angle grinders/straight grinders


L 14-11 125
LE 14-11 125





SPECIFICATIONS

Max. disc diameter	125 mm
No load speed L 14-11 125	11500 rpm
No load speed LE 14-11 125	2800-11500 rpm
Power input	1400 watt
Power output	880 watt
Tool fixture	M 14
Size (L x H)	310 x 105 mm
Cable length	4.0 m
Weight	2.3 kg





1400 watt angle grinder with superior torque, 125 mm

- Microprocessor control with soft start, restart protection after power failure, temperature monitoring, CDC-electronic feedback control
- Highly efficient and resilient motor for more power output
- Longer service life thanks to optimised cooling and revised carbon geometry
- Extensive dust protection for motor and gears
- Compact, narrow and ergonomic shape
- Anti-Kickback – this shuts down the motor on the disc being blocked
- Tool-free adjustment of safety guard
- Lockable slide switch
- Spindle lock
- This universal angle grinder is suited for steel/metal surface finishing, for work on the site/renovation as well as for vehicle bodywork and construction firms
- SoftVib handgrip with integrated, patented locknut wrench and vibration damping
- Please note the maximum speed (rpm) of the accessories
- This machine is also available in 110 V (only LE 14-11 125)

Standard equipment	Order no.
L 14-11 125	**447.560**
1 guard grinding 125 Ø	436.860
1 SoftVib handle	316.857
1 clamping flange	335.282
1 clamping nut M14	100.080
LE 14-11 125	**447.587**
1 guard grinding 125 Ø	436.860
1 SoftVib handle	316.857
1 clamping flange	335.282
1 clamping nut M14	100.080

Accessories from page 27