www.flex-tools.com

this is proformance FLEX

GE 6 X 18-EC

18 V Cordless wall and ceiling sander – random-orbit Giraffe®

Order no. 535802

GTIN 4030293296428





- The random orbital movement is ideal for controlled guidance on the surface, a fine sanding pattern and working close to the edge. This delivers perfect surface finishing
- Light weight: Carbon is a very light material, making the wall and ceiling sander's overall weight much lighter. This reduces the stress on the user and minimises fatigue during sanding over longer periods
- This unusually light machine offers unique user comfort. The wall and ceiling sander is optimally balanced, which enables perfect guidance as the weight is evenly distributed across the sander. Extremely pleasant to handle thanks to the ergonomically-shaped carbon guide tube and the soft grip insert on the main handle and the spade handle
- Powerful – with a brushless motor – and flexible – with no cumbersome cable – the GE 6 X cordless wall and ceiling sander offers the ideal conditions for professional use on the building site
- With wear-free disk brake for controlled contact with the surface to prevent damage
- A very flat, gimbal-mounted sanding head with a swivel range of 160° enables high flexibility and optimum adjustment when sanding on walls and ceilings
- The sanding head with the innovative backing pad adapts very well to the surface being sanded, and delivers a noticeably improved sanding feel. The great flexibility of the Giraffe® means that no unnecessary pressure needs to be applied in order to achieve optimum results
- Variable speed, levels from 1-6 with Power Control LED indicator
- According to the assortment of sanding paper ideally suited for sanding plaster boards, solid styropor insulation slabs, preparation for painting
- Very effective suction extraction thanks to a special hole pattern in the backing pad prevents clogging of the sanding pad to ensure dust-free working
- Very flexible thanks to an optional 500 mm extension (accessory) for high rooms, can be attached without any tools
- Connection option for the FLEX safety vacuum cleaners with flow rate optimisation on the guide tube with the FLEX clip system, anti-static in conjunction with an antistatic suction hose.
- LED battery capacity display
- FLEX battery system: suitable for all FLEX 18 V battery packs. Delivery does not include battery and charger
- For even greater precision, an optional light ring can be fitted to the grinding head of the GE 6 X. This reveals any unevenness whilst sanding, thereby eliminating the need for further finishing work

Technical data

Battery voltage	18 V
Backing pad diameter	225 mm
No-load speed	5600 - 8500 rpm
Orbit rate, no load	11200 - 17000 rpm
Stroke	4 mm
Head angle of inclination	160°
Tool holder, wall and ceiling sander	hook and loop
Length	1500 mm
Weight without battery pack	3.21 kg

Standard equipment