FLEX-Elektrowerkzeuge GmbH
Bahnhofstraße 15
71711 Steinheim
Phone +49 7144 828-0
Fax +49 7144 25899
info@flex-tools.com
www.flex-tools.com

Accessories

SDS 4-max drill



Technical attributes			
Diameter in mm	Length in mm	QTY/PKG	Order number
16	340	1	368.261
18	340	1	368.288
20	320	1	368.296
22	320	1	368.318
25	320	1	368.326
28	370	1	368.334
30	370	1	368.342
32	370	1	368.350
35	370	1	368.369
16	540	1	368.377
18	540	1	368.385
20	520	1	368.393
22	520	1	368.407
24	520	1	368.415
25	520	1	368.423
28	570	1	368.431
30	570	1	368.458
32	570	1	368.466
35	570	1	368.474
40	570	1	368.482

The drill tipped 4-cut head design ensures centric guidance in the drill hole. Two additional secondary cutters protect the drill from impacting on any steel reinforcement. Moreover, the special spiral design reduces vibrations. Highly suitable for drilling in reinforced concrete.

Drill dust adapter

Order number 394.025



Technical attributes	
Dimensions in mm	290 x 65
QTY/PKG	1

The drill dust extractor is connected to the suction hose of the FLEX vacuum cleaners or to different adapters so that the dust is extracted directly through the drill hole. There is no dust residue. For drilling applications up to Ø 24 mm.