www.flex-tools.com

this is proformance FLEX

OSE 2-70x198 18-EC C

Compact cordless orbital sander with speed control 18 V

Order no. 534435

GTIN 4030293282759



- Lightweight, compact one-handed orbital sander, very ergonomic and low-vibration thanks to special balancing for fatigue-free and joint-friendly work
- Ideal for sanding filled surfaces on car parts during repair work. For surface sanding the substrate and avoiding unevenness before applying the filler and using a random orbit sander
- E-signal switch for simple, safe operation with quick-stop function prevents trailing of the backing pad
- Brushless motor with greater efficiency and a longer service life
- Electronics: Speed preselection with 4 settings
- Sanding speed suitable for the material thanks to electronic speed adjustment
- Velcro backing pad with bevelled pad geometry and multi-hole system for optimum suction, suitable for all commercially available pads
- Ergonomically designed, handy grip cover with soft grip insert ensures a secure grip and good guidance
- External dust extraction Ø 27 mm, antistatic suction hose SH 27x3,5m AS (445.045) can be connected
- Integrated dust extraction with dust filter bag
- Electronic management system (EMS) protects the machine, extends the service life, and increases efficiency
- LED battery capacity display
- FLEX battery system: suitable for FLEX 18,0 V/5,0/2,5 Ah battery packs. Delivery does not include battery and charger



Technical data

Battery voltage	18 V
Battery capacity	2.5 / 5.0 Ah
Stroke	2 mm
Backing pad length	198 mm
Backing pad width	70 mm
Orbit rate, no load	12000 - 20000 rpm
No-load speed	6000 - 10000 rpm
Diameter dust extraction connection	Ø 27
Dimensions WxLxH	238 x 75 x 140 mm
Weight without battery pack	1.12 kg

Standard equipment

1 Dust bag (532093)
1 Adapter, short (532094)
1 Adapter, long (532095)