
NEW





ALC 3/360-G/R 10.8 Set
360° cross-line laser with receiver mode
Order no. 500739

Standard Equipment:
1 laser target plate and goggles (500.763) ·
1 laser universal bracket (500.747) ·
1 battery 2.5 Ah AP 10.8/2.5 (418.048) ·
1 charger CA 10.8 (418.021) ·
1 carrying case L-BOXX® 136 (414.085)

NEW





RC-ALC 3/360
Laser receiver
Order no. 500755

Precision	± 0,5 mm/10 m, ± 3,2 mm/50 m
Max. working range	5-70 m
Operation duration	15 h
Integrated battery	Batteries 9V-unit
Weight	0,15 kg
Product Key	115

Standard Equipment:
Batteries 9V-unit (1 piece) ·
1 holder (1 piece)

NEW





ALC 2/1-G/R
Self-levelling crossline laser with receiver mode
Order no. 509833

Number of lines	1 horizontal/1 vertical
Visible area lines	110°
Precision	± 0,3 mm/m
Self-levelling range	± 4 °
Max. working range	50 m
Max. range with receiver	70 m
Operation duration with battery drive	4 - 10 h
Temperature range	-5° - +50 °C
Laser class	2
International Protection	IP 54
Integrated battery	3,7 V 1200 mAh / Li-Ion
Size (W x L x H)	57 x 96 x 96,5 mm
Weight	0,36 kg
Product Key	115

Standard Equipment:
1 wall bracket magnetic WB-M/S 1/4 ALC-Basic (428.167) ·
1 USB-cable (1 piece) ·
1 USB-charger (1 piece) ·
1 carrying bag (1 piece)

NEW





ALC 3/1-G/R
Self-levelling crossline laser with receiver mode
Order no. 509841

Number of lines	1 horizontal/ 2 vertical plus plumb
Visible area lines	110°
Precision	± 0.3 mm/m (plumb ± 0,6 mm/m)
Self-levelling range	± 4 °
Max. working range	20 m / plumb 5 m
Max. range with receiver	70 m
Operation duration with battery drive	5 - 11 h
Temperature range	-5° - +50 °C
Laser class	2
International Protection	IP 54
Integrated battery	3,7 V 2000 mAh / Li-Ion
Size (W x L x H)	60 x 112 x 126 mm
Weight	0,53 kg
Product Key	115

Standard Equipment:
1 wall bracket magnetic WB-M/S 1/4 ALC-Basic (428.167) ·
1 USB-cable (1 piece) ·
1 USB-charger (1 piece) ·
1 carrying bag (1 piece)





ADM 60 Li
Laser range finder
Order no. 447862

Precision	± 3 mm
Max. working range	0,15 - 60 m
Laser class	2
Visible laser diodes	< 1 mW, 635 nm
International Protection	IP 54
Integrated battery	3,7 V 500 mAh / Li-Ion
Size (W x L x H)	30 x 56,5 x 122 mm
Weight	0,13 kg
Product Key	115

Standard Equipment:
1 USB-cable (1 piece) ·
1 USB-charger (1 piece) ·
1 carrying bag (1 piece)