www.flex-tools.com

this is proformance FLEX

LD 16-8 125 R, Kit E-Jet


Compact renovation grinder for dust-free grinding close to edges, 125 mm

Order no. 504955

GTIN 4030293230705



- Electronic control: with tachogenerator constant speed control, soft start, overload protection and temperature monitoring
- Dust extraction: prevents dust nuisance, reduces disc wear, keeps the concrete pores open for the new coating
- Reliable 1600 watt high-performance motor with sufficient power reserves
- Anti-Kickback - this shuts down the motor on the disc being blocked
- Guard with pivoting segment to allow grinding right up to the wall. Height-adjustable to the disc height and for optimum dust extraction
- With steplessly adjustable, vibration-proof, ergonomic bail handle, for optimum handling and machine control
- For fast hose connection. FLEX clip connection for Ø 32 mm snap connection included in the standard equipment
- Recessed spindle lock, to avoid unintentional activation
- Ideally suited for processing walls, ceilings and floors. Efficient and economic working thanks to optimum coordination between machine and sanding disc
- Grinding disc for abrasive materials. For removal of formwork transitions and concrete runs from freshly concreted surfaces, mineral adhesives, screeds, plaster, mortar, abrasive lime sand brick, sandstone, chamotte, asphalt.



Technical data

Power consumption	1600 W
Power output	950 W
Voltage	230 V
Frequency	50/60 Hz
Disc diameter	125 mm
No-load speed	7800 rpm
Tool holder, renovation grinder	M14
Cable length	4.0 m
Weight	3.1 kg

Standard equipment

1 Screed-Jet diamond grinding disc (359394)
1 Extraction hood with pivoting edge segment (498475)
3 Cable clip (252188)
1 Hexagon socket wrench (102229)
1 Face pin spanner (392537)
1 Carrying case L-BOXX® (414093)
1 Case insert (414131)
1 Bail handle