www.flex-tools.com

this is proformance FLEX

CS 60 WET

Diamond stone cutter for wet cuts, mitre cuts up to 45 °, with GFCI circuit breaker

Order no. 374016

GTIN 4030293152311



- Ideal for: Inserting water grooves in window sills or steps, work tops, facade slabs, terazzo slabs in garden design & landscaping, joint renovation in the floor
- GFCI operator protector circuit breaker: integrated in cord
- Quick-fit brass coupling: for 1/2 water hose
- High-performance motor: extra powerful for stone cutting and joint milling
- Continuous cut depth setting from 0-60 mm, with rail guide up to 54 mm. In the mitre cut from 0-44 mm, with guide rail up to 38 mm
- Continuous angle adjustment for mitre cuts from 0-45°
- Cut marking at the base plate from 0°/30°/45° for rapid orientation
- High-quality magnesium die-castings for protective cover and base plates
- Motor protection made of rubber prevents the direct intake of spray water
- Water supply: for an effective cooling of the diamond blade
- Spindle lock



Technical data

Power consumption	1400 W
Power output	840 W
Voltage	230 V
Frequency	50/60 Hz
Cutting depth	60 mm
Cutting depth with guide rail	54 mm
Cutting depth, mitre cut (45°)	5-44 mm
Cutting depth, mitre cut with guide rail (45°)	38 mm
No-load speed	6200 rpm
Diamond disc diameter	170 mm
Diamond disc hole	22.2 mm
Pivoting range	45°
Cable length	4.0 m
Dimensions WxLxH	360 x 280 x 170 mm
Weight	4.5 kg

Standard equipment

1 Diamond cutting disc (347515)
1 Key SW 5 - screw drivers (359343)
1 Parallel stop (350613)
1 Carrying case L-BOXX® (414093)
1 Case insert (436771)