www.flex-tools.com

this is proformance FLEX

KNE 16 18.0-EC


Cordless nibbler 18 V

Order no. 532068

GTIN 4030293259089



- Good curve mobility for notches and internal cut-outs from radii of 40 mm or more
- Quick, tool-free adjustment of the cutting direction up to 360° in 45° increments
- Cutting with no distortion and sparks and without annoying metal dust in both flat and shaped metal sheets
- Extremely streamlined handle section with soft-grip inlays for perfect handling
- Brushless motor with greater efficiency and a longer service life
- Electronics: Speed preselection in 4 steps, CDC constant electronics, soft start, overload protection, restart lock, temperature monitoring
- Anti-Kickback - this shuts down the motor on the tool being blocked
- On/off switch with lock and protection
- LED battery capacity display
- FLEX battery system: suitable for all FLEX 18 V battery packs. Delivery does not include battery and charger



Technical data

Orbit rate, no load	1950-4250 1 rpm
Max. metal sheet thickness, steel 400 N/mm2	1.6 mm
Max. metal sheet thickness, steel 600 N/mm2	1.0 mm
Max. metal sheet thickness, steel/stainless steel 800 N/mm2	0.7 mm
Max. metal sheet thickness, aluminium 250 N/mm2	2.0 mm
Smallest radius	24 mm
Min. starting hole diameter	22 mm
Diameter of smallest cuttable hole	48 mm
Distance for template cutting	1.5 mm
Working speed	2,2 m/min
Battery voltage	18 V
Battery capacity	2.5 / 5.0 / 8.0 Ah
Weight without battery pack	1.5 kg
Sound pressure level	93.8 dB(A)
Vibration	17.1 m/s^2

Standard equipment

1 Carrying case L-BOXX® (414085)
1 Case insert (535184)