

Constant Drive Control · Soft Start · Speed Selection · Overload Protection · Side handgrip · 4 m Mains cable

LBR 1506 VRA
1200 watt weld and pipe belt sander
Order no. 282499

Power input	1200 watt
Power output	700 watt
Belt speed max.	30 m/sec
Belt speed min.	10 m/sec
Belt width	40 mm
Belt length	618 mm
Cable length	4,0 m
Size (W x L x H)	495 x 150 x 115 mm
Weight	4,2 kg
Product Key	104

Standard Equipment:
1 side handle (252.721) ·
1 sanding belt ZIRCOFLEX P 60 (445.061) ·
1 sanding belt ZIRCOFLEX P 120 (266.132) ·
1 sanding belt MESHFLEX A 240 (317.977) ·
1 hexagon socket wrench, SW 5 (115.460) ·
1 hexagon socket wrench, SW 6 (104.167) ·
1 hexagon socket wrench, SW 3 (178.772)



Restart Protection · Soft Start · Speed Selection · Hook and loop fasteners · 4 m Mains cable

ST 1005 VE
Finger sander
Order no. 259540

Power input	400 watt
Power output	220 watt
Sanding medium	39 x 60 mm
Orbit	8 mm
Orbit rate, no load	1200-4500 opm
Cable length	4,0 m
Dimensions in mm	450 x 70 mm
Weight	2,2 kg
Product Key	104

Standard Equipment:
2 polishing shoes with velcro polishing cushion (1 set) ·
10 hook-and-loop sand papers, P 60 (258.299) ·
10 hook-and-loop sand papers, P 120 (258.300) ·
10 hook-and-loop sand papers, P 180 (258.301) ·
10 hook-and-loop fleece, A 240, 39 x 60 mm (258.302) ·
1 hexagon socket wrench, SW 3 (217.794)

Accessories for metal surface finishing

Accessories INOXFLEX LE 14-7 125



Thin cutting disc (1 mm) for stainless steel/steel
Product Key 220

Designation	Dimensions in mm	QTY/ PKG	Order no.
TSC Inox 125x1x22,2 VE10	125 Ø x 1 x 22,2	10	349836



Flap disc for metal and stainless steel, cambered
Product Key 222

Designation	Dimensions in mm	Grit	QTY/ PKG	Order no.
FSC K60 125x22,2 VE10	125 Ø x 22,2	P 60	10	349925
FSC K80 125x22,2 VE10	125 Ø x 22,2	P 80	10	349933



SC-VL polishing flap wheel for metal and stainless steel, cambered
Product Key 222

Designation	Dimensions in mm	Grit	QTY/ PKG	Order no.
VFSC SC-M 125x22,2 VE5	125 Ø x 22,2	medium	5	358606



Fillet disc
Product Key 225

Designation	Dimensions in mm	Grit	QTY/ PKG	Order no.
KSC 6A-M 125x6x22,2 VE10	125 Ø x 6 x 22,2	6 A medium	10	358711
KSC 3S-F 125x6x22,2 VE10	125 Ø x 6 x 22,2	3 S fine	10	358703



Grinding disc PYRAFLEX
Product Key 200

Designation	Dimensions in mm	Grit	QTY/ PKG	Order no.
D125 PY-A30 VE10	125 Ø	A 30 (K 600)	10	358819
D125 PY-A45 VE10	125 Ø	A 45 (K 400)	10	358800
D125 PY-A65 VE10	125 Ø	A 65 (K 280)	10	358797
D125 PY-A160 VE10	125 Ø	A 160 (K 120)	10	364592