Type	Description	Designation	Type	QP	Order no.	GE 7	GE 5 / GE 5 R	GSE 5 R	WSE 7 Vario Set / Plus	WST 700 VV / Plus
Velcro backing pad Ø 225, round 	Hard backing pad with high removal rate, with use with velcro backed abrasives. Recommended for use with dimond grinding pads Ø 225.	SP-H D225-10	hard	1	350.362	-	-	-	■	■
	Medium backing pad for sanding down soft fillers. Velcro system for fixing of abrasives. Recommended for use with dimond grinding pads Ø 225.	SP-M D225-10	medium	1	352.306	-	-	-	■	■
	Soft. Highly flexible backing pad. Facilitates handling and allows for sensitive working. Prevents damage (swirl marks) when the pad touches the surface. For use with velcro backed abrasives.	SP-S D225-10	soft	1	366.862	-	-	-	■	■
	Supersoft. The sanding disc enables extremely gentle positioning on the wall. The set consists of a backing pad, Velcro adapter (KAD D225/16), clamping disc and screw. For GE 5 / R, GSE 5, GE 7.	KAD D225/16 Set	supersoft	1	483.486	■	■	■	-	-
	Supersoft. The sanding disc enables extremely gentle positioning on the wall. The set consists of a backing pad, Velcro adapter (KAD D225/13), clamping disc and screw. For WST 700 VV, WSE 7.	KAD D225/13 Set WST700, WSE7	supersoft	1	441.120	-	-	-	■	■
	Backing pad for linishing surfaces in Q3 and Q4 quality. Sanding disc attached with velcro system. Can be used with the GE 7 random-orbital sanding head (MH-X D225).	SP-X D225		1	472.603	■	-	-	-	-
Velcro triangular backing pad 	Backing pad for plaster or hard filler compounds in drywall construction, for use with velcro backed abrasives.			1	354.988	-	-	-	■	■
		SP-T 290x290		1	472.611	■	-	-	-	-
Interface Ø 225, round 	Interface as absorbing element between grinding pad and abrasive paper. Ideal for finishing surfaces. Improves the dust extractor action and lengthens the service life of the sanding disks. Recommendation: work with interface for in-between and final sanding involving finer grain. Do not work with interface for rough sanding involving coarse grain and when using sanding fleece.	IP D225-10 VE2		2	470.678	■	■	■	■	■