

Fast clip adapter

Product key 263

Change adapter on electric power tools with closed FLEX clip-system for quick and easy detachment/attachment (quick clamping ring).

Designation	Order no.	GTIN	Qty.
SAD-FC 32	410497	4030293175105	1



Carrying case

Product key 299

Made of shock-resistant plastic for the WST and WSE 7 as well as for sanding tools and exchangeable heads.

Designation	Order no.	GTIN	Qty.
TK-S WST/WSE7	389986	4030293162495	1

Accessories RETECFLEX



Hook-and-loop backing pad Ø 115, Bowl

Product key 205

Backing pad with hook-and-loop face Bowl for securing the abrasives with the hook-and-loop system. As damping elements 12 mm cellular rubber pads ensure uniform pressure distribution.

Designation	Diameter	Qty.	Order no.	GTIN	Qty.
BP-M RE D115 M14	115 mm	1 Cont.	503754	4030293229754	1



Base for scouring work

Product key 229

Tool-free interchangeable protective guard for optimally guiding the machine and effective dust extraction.

Designation	Order no.	GTIN	Qty.
STF D80 RE	369314	4030293150560	1



Extraction hood

Product key 229

With swivel segment and brush ring for grinding work.

Designation	Diameter	Order no.	GTIN	Qty.
SG-R D115 RE	115 mm	366528	4030293144439	1



Brush ring

Product key 300

Brush ring for dust extraction hood - contains two segment parts.

Designation	Order no.	GTIN	Qty.
BK-H RE14-5-115	369454	4030293147607	1



Face pin spanner

Product key 299

Special spanner for removing the scouring and grinding heads.

Designation	Order no.	GTIN	Qty.
STL-RE	366536	4030293144446	1



Carrying case L-BOXX®

Product key 299

The robust storage and transport system L-BOXX® made of impact-resistant plastic conveys tools, accessories and consumables easily and comfortably to the place of use. Elaborate inserts provide order and clarity, ergonomically shaped handles and additional moulded recesses for flexible and comfortable handling. The unbeatably simple connection and disconnection of the different L-BOXXes optimises combined transportation. Fits the TÜV-tested in-vehicle equipment system from Sortimo perfectly and without adapters. Load capacity per L-BOXX® up to 25 kg, combined transportation up to 40 kg, the cover can be loaded up to 100 kg. Splash-proof. Without insert.

Designation	Internal dimensions L x W x H	Dimensions WxLxH	Weight	Order no.	GTIN	Qty.
TK-L 238	378 x 306 x 209 mm	442 x 357 x 253 mm	2.8 kg	414093	4030293177444	1

Case insert

Product key 299

Matching insert for RETECFLEX for carry case L-BOXX® 238.

Designation	L-Boxx type	Order no.	GTIN	Qty.
TKE RE 14-5	238	414182	4030293177529	1