Range of Products

Valid from 1. February 2024



Inox Set (Ø 125 mm)

Product key 209

Set for processing metal surfaces for the SUPRAFLEX. Consisting of: 1 carrying case L-BOXX® 102, 1 case insert accessory TKE 4xD130/ 1x135x295, 3 sheets of hook-and-loop sandpaper CORKFLEX, grit sizes P 280, P 400, P 800, 10 sheets of hook-and-loop sandpaper CERAFLEX K 80, K 120, K 180, 1 SC fleece disc in coarse, medium, very fine, 1 hard felt pad, 1 soft felt pad, 1 clamping flange CF SE 14-2, 1 clamping nut.

Designation	Order no.	GTIN	Qty.
I-Box SE 14-2 125	393428	4030293165250	1



Stone Set (Ø 125 mm)

Product key 209

Stone processing set for the SUPRAFLEX. Consisting of: 1 carrying case L-BOXX® 102, 1 case insert accessory TKE 4xD130/ 1x135x295, 1 diamond grinding pad, grit sizes 50, 100, 400, 800, 3000, 1 hard felt pad, 1 soft felt pad.

Designation	Order no.	GTIN	Qty.
S-Box SE 14-2 125	393444	4030293165274	1



Hook-and-loop backing pad

Product key 205

With 8-hole system for optimum dust extraction for all FLEX hook-and-loop sanding tools Ø 125 mm. The 3 mm cellular rubber damping reduces the shearing forces between support pad and sanding tool. Thanks to long hooks, there is greater temperature resistance at a high load.

Designation	Diameter	Order no.	GTIN	Qty.
SP D125-8 H/F M14	125 mm	391727	4030293165199	1



Hook-and-loop backing pad

Product key 205

With 6 + 8-hole system for optimum dust extraction for all FLEX hook-and-loop sanding tools Ø 150 mm. The 3 mm cellular rubber damping reduces the shearing forces between support pad and sanding tool. Thanks to long hooks, there is greater temperature resistance at a high load.

Designation	Diameter	Order no.	GTIN	Qty.
SP D150-8/6 H/F M14	150 mm	419192	4030293181267	1



Disc brush

Product key 209

Ideal for brushing off glazed wood surfaces, brushing and deburring metallic surfaces and edges, cleaning natural stone surfaces as well as cleaning and structuring natural wood surfaces. The 50 mm brush height ensures a flexible processing of shapes and contours. The carrier and the bristles are characterised by high rigidity, strength, hardness and removal rate for a long service life and maximum efficiency. To avoid damage, the maximum speed of 2500 rpm must not be exceeded.

Designation	Order no.	GTIN	Qty.
BT-NY D130/50 P46 M14	409030	4030293174245	1



Extraction hood with pivoting edge segment

Product key 229

Enables you to work near edges at maximum extraction power. Tool-free height adjustment via clamping lever allows quick adjustment of the extraction hood to the tool height.

Designation	Diameter	Order no.	GTIN	Qty.
SG-R D125 SE/LD	125 mm	393363	4030293165229	1



Extraction hood with pivoting edge segment

Product key 229

For optimal dust extraction without adapter. Enables you to work near edges at maximum extraction power. Tool-free height adjustment via clamping lever allows quick adjustment of the extraction hood to the tool height.

Designation	Diameter	Order no.	GTIN	Qty.
SG-R D150 SE	150 mm	419176	4030293181243	1



Antistatic suction hose with auxiliary air control

Product key 262

Internal Ø 32 mm, 4 m with universal device connection, snap connection and universal adapter (445.029), antistatic. Includes variable adjustment of suction power for reduction of vacuum.

Designation	Order no.	GTIN	Qty.
SH-C 32x4m AS/NL	406708	4030293172814	1



Handle

Product key 300

Side handle, thread M 8.

Designation	Order no.	GTIN	Qty.
GS-SP M8	450774	4030293199767	1