Adapter



SDS-plus M14 adapter
Product Key 239

	QTY/ PKG	Order no.		
	1	374091		



Extension M14
Product Key 249

Designation	Dimensions in mm	QTY/ PKG	Order no.		
R-V 400 M14 M/F	400	1	374113		

Measuring technology/laser






ALC 8
Self-levelling multi-line laser for visual room layout
Order no. 458600

Number of lines	1 horizontal 360°/ 4 vertical plus plumb
Visible area lines	360°/90°
Precision	± 0.3 mm/m (plumb ± 0,6 mm/m)
Self-levelling range	± 3 °
Max. working range	20 m / plumb 5 m
Operation duration	6 h
Temperature range	-10° - +45 °C
Laser class	2
International Protection	IP 54
Integrated battery	3,7 V 1200 mAh / Li-Ion
Size (L x H)	130 x 220 mm
Weight	1,2 kg
Product Key	115

Standard Equipment:
1 USB-cable (1 piece) ·
1 USB-charger (1 piece) ·
1 carrying case (1 piece)

NEW





ALC 3/360-G/R 10.8
360° cross-line laser with receiver mode
Order no. 490261

Battery voltage	10,8 V
Battery capacity	2,5 / 4,0 Ah
Number of lines	1 horizontal/2 vertical
Visible area lines	360°
Precision	± 0,3 mm/m
Self-levelling range	± 4 °
Max. working range	100 m
Max. range with receiver	120 m
Operation duration with battery drive	6,5 - 12 h
Temperature range	-10° - +40 °C
Laser class	2
International Protection	IP 54
Size (W x L x H)	152 x 88 x 130 mm
Weight without battery	0,8 kg
Product Key	115

Standard Equipment:
1 laser target plate and goggles (500.763) ·
1 laser universal bracket (500.747) ·
1 carrying case L-BOXX® 136 (414.085)